ART139

ATCA Rear Transition Module (RTM) for ATC139



Key Features

- AdvancedTCA RTM for ATC139
- Dual RJ-45 (GbE)
- RS-232 interface for RTM Management
- DSUB-26 interface to both Shelf Managers (on ATC139)
- IPMI 2.0 compliant

Benefits

- Expertise in RTM design
- Full ecosystem of AdvancedTCA switches, processors, chassis platforms, and specialty blades
- Design utilizes proven VadaTech subcomponents and engineering techniques
- Electrical, mechanical, software, and system-level expertise in house
- AS9100 and ISO9001 certified company



ART139

The ART139 is an I/O expansion ATCA Rear Transition Module (ARTM) that provides GbE, and Management I/O for the front blade. The module is designed to mate with the ATC139 ATCA Carrier.

The module has dual GbE ports which route to the host via the Zone 3 connectors and provides dual RJ-45 to the RTM front panel.

The ART139 also provides a management RS-232 port and access to dual Shelf Managers on ATC139.



Block Diagram




Figure 1: ART139 Functional Block Diagram

Specifications

| Architecture | | | |
|-------------------|---|---|--|
| Physical | Dimensions | Weight: 0.8 lbs (362.87 g) | |
| | | Width: 12.69" (322.25 mm) | |
| | | Depth: 3.7" (94 mm) | |
| Туре | ATCA RTM | Rear I/O module for ATC139 | |
| Standards | | | |
| PICMG | ATCA | PICMG 3.0 revision 2.0 | |
| Module Management | IPMI | IPMI version 2.0 | |
| Ethernet | | GbE | |
| Configuration | | | |
| Power | ART139 | ~1 W | |
| Environmental | Temperature | Operating temperature: -5° to 45° C (55°C for limited time, performance restrictions may apply), industrial and extended versions also available (See environmental spec sheet) | |
| | | Storage Temperature: -40° to +90°C | |
| | Vibration | Operating 9.8 m/s² (1G), 5 to 500Hz on each axis | |
| | Shock | Operating 30G on each axis | |
| | Relative Humidity | 5 to 95 per cent, non-condensing | |
| Front Panel | Interface Connectors | Dual RJ-45 for GbE | |
| | | DSUB-26 for ShMM | |
| | | Micro USB for RS-232 | |
| | LEDs | IPMI management control | |
| | Mechanical | Hot swap ejector handle | |
| Software Support | Operating System | Agnostic | |
| Conformal Coating | | Humiseal 1A33 Polyurethane (Optional) | |
| | | Humiseal 1B31 Acrylic (Optional) | |
| Other | | | |
| MTBF | MIL Hand book 217-F@ TBD hrs | | |
| Certifications | Designed to meet FCC, CE and UL certifications, where applicable | | |
| Standards | VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards | | |
| Warranty | Two (2) years | | |
| | | | |

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and µTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Ordering Options

ART139 - 000-000-00J

| | J = Temperature Range and Coating |
|--|--|
| | 0 = Commercial, No coating 1 = Commercial, Humiseal 1A33 polyurethane 2 = Commercial, Humiseal 1B31 acrylic 3 = Industrial, No coating 4 = Industrial, Humiseal 1A33 polyurethane 5 = Industrial, Humiseal 1B31 acrylic 6 = Extended, Humiseal 1A33 polyurethane 7 = Extended, Humiseal 1B31 acrylic |

Related Products

ATC139



- Carrier for dual Shelf Manager slots (VadaTech's VT011)
- PICMG 3.0 Rev 3.0 compliant
- Redundant failover between the two shelf managers

VT830



- 19" rackmount 6U ATCA Chassis with integrated Switch and Shelf Manager
- 10GbE/GbE Managed Layer 2
- 40GbE/10GbE/GbE Managed Layer 3





- Shelf manager for AdvancedTCA systems
- Utilizing VadaTech Third Generation Shelf Manager VT003
- Quad Core ARM Freescale processor @ 1 GHz per core

Contact

VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014 Phone: +1 702 896-3337 | Fax: +1 702 896-0332

Asia Pacific Sales Office

7 Floor, No. 2, Wenhu Street, Neihu District, Taipei 114, Taiwan Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR Phone: +44 2380 016403

info@vadatech.com | www.vadatech.com

Choose VadaTech

We are technology leaders

- · First-to-market silicon
- Constant innovation
- · Open systems expertise

We commit to our customers

- · Partnerships power innovation
- · Collaborative approach
- Mutual success

We deliver complexity

- · Complete signal chain
- · System management
- · Configurable solutions

We manufacture in-house

- Agile production
- · Accelerated deployment
- AS9100 accredited





Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc.

Other registered trademarks are the property of their respective owners.

AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved.

Specification subject to change without notice.