

Architecture		
Physical	Dimensions	Single-width, half-height option for mid or full-height
		Width: 2.89 in. (73.5 mm)
		Depth: 7.11 in. (180.6 mm)
Product Type	AMC Clock	Telco/Fabric Control/Monitor
Standards		
AMC	Type	AMC.0
Module Management	IPMI	IPMI Version 2.0
Configuration		
Power	AMC002	2W
Environmental	Temperature	Operating Temperature: -20° to 75° C
		Storage Temperature: -40° to +95° C
	Vibration	1G, 5-500Hz each axis
	Shock	30G each axis
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel	Interface Connector	RS-232
		5 SMB for clock input/output
	LEDs	IPMI Management Control
		Clock Status
	Mechanical	Hot-swap ejector handle
Other		
MTBF	MIL Hand Book 217-F > TBDHrs.	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years.	
Trademarks	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.	