

## Architecture

Physical	Dimensions	Single-width, half-height, option for mid or full-height Width: 2.89 in. (73.5 mm) Depth: 7.11 in. (180.6 mm)
Product Type	AMC Clock	GPS Clock

## Standards

AMC	Type	AMC.0
Module Management	IPMI	IPMI Version 2.0

## Configuration

Power	AMC003	1.5W
	Temperature	Operating Temperature: -20° to 75° C Storage Temperature: -40° to +95° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30G each axis
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel		IPMI Management Control
	LEDs	Clock status
	Connectors	Three SMB

## Other

MTBF	MIL Hand Book 217-F > TBDHrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years.
Trademarks	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.