

# Specifications

Architecture	
<b>Physical</b>	<b>Dimensions</b> Double module, full-size option Width: 5.85" (148.5 mm) Depth 7.11" (180.6 mm)
Standards	
<b>AMC</b>	<b>Type</b> AMC.0
<b>Module Management</b>	<b>IPMI</b> IPMI v2.0
Configuration	
<b>Power</b>	<b>AMC014</b> ~0.3W
<b>Environmental</b>	<b>Temperature</b> See <a href="#">Ordering Options</a> and <a href="#">Environmental Spec Sheet</a> Storage Temperature: -40° to +85°C
	<b>Vibration</b> Operating 9.8 m/s <sup>2</sup> (1G), 5 to 500Hz on each axis
	<b>Shock</b> Operating 30Gs on each axis
	<b>Relative Humidity</b> 5 to 95% non-condensing
<b>Front Panel</b>	<b>Interface Connectors</b> SMPM: Trig Out Micro USB for MGT RS-232 and Trigger Controller RS-232
	<b>LEDs</b> IPMI management control LEDs 3 Activity/status LEDs
	<b>Mechanical</b> Hot-swap ejector handle
<b>Software Support</b>	<b>Operating System</b> Independent
Other	
<b>MTBF</b>	MIL Hand book 217-F@ TBD hrs
<b>Certifications</b>	Designed to meet FCC, CE and UL certifications, where applicable
<b>Standards</b>	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
<b>Warranty</b>	Two (2) years, see <a href="#">VadaTech Terms and Conditions</a>

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.