

Architecture

Physical	Dimensions	Single-Width, Half-Height (with Mid or Full-Height options)
		Width: 2.89 in. (73.5 mm) Depth: 7.11 in. (180.6 mm)
Type	AMC Input	16 total inputs

Standards

AMC	Type	AMC.0
Module Management	IPMI	IPMI Version 2.0

Configuration

Power	AMC090	3.5W IPMI Controller < 30 mA @3.3V
		Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 200 LFM)
Environmental	Temperature	Storage Temperature: -40° to +90° C
	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel	Interface Connectors	51-Pin Micro DIN style
	LEDs	IPMI Management Control

Other

MTBF	MIL Hand Book 217-F > TBDHrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years.
Trademarks	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.