

AMC 24-channel Isolated (12 drive, 12 sink) Output Module – AMC099

SPECIFICATIONS

Architecture		
Physical	Dimensions	Width: 2.89" (73.5 mm)
		Depth 7.11" (180.6 mm)
		Single module, compact size (mid and full size options available)
Type	AMC Input	24 optically isolated outputs: Twelve outputs are current source based on isolated outputs and twelve outputs are current sinks. Multiple outputs will change state with a single write.
Standards		
AMC	Type	AMC.0 and AMC.1
Module Management	IPMI	IPMI v2.0
PCIe	Lanes	x4
Configuration		
Power	AMC099	3W
Environmental	Temperature	Operating temperature: -5° to 45°C (55°C for limited time, performance restrictions may apply), (See environmental spec sheet)
		Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock	Operating 30Gs each axis
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	51-pin Micro DIN connector
	LEDs	IPMI management control Activity/Link/Status LEDs
	Mechanical	Hot-swap ejector handle
Software Support	Operating System	Independent
Other		
MTBF		MIL Hand book 217-F@ 242,000 hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty		Two (2) years, see VadaTech Terms and Conditions
Trademarks and Disclaimer		The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice