

SPECIFICATIONS

Architecture		
Physical	Dimensions	Double module, mid-size (full-size optional) Width: 5.85" (148.5 mm) Depth 7.11" (180.6 mm)
	Type	AMC Carrier AMC site carrier for PMC/XMC modules
Standards		
AMC	Type	AMC.1
Module Management	IPMI	IPMI version 2.0
PCIe	Lanes	x4
Configuration		
Power	AMC105	Application specific
Environmental	Temperature	Operating temperature: -5° to 45°C (55°C for limited time, performance restrictions may apply), (See environmental spec sheet) Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1.0 G), 5 to 500Hz
	Shock	30Gs on each axis
	Relative Humidity	5 to 95 per cent, non-condensing
Front Panel	Interface Connectors	Mini SCSI Type Connector
	LEDs	IPMI management control Activity/Status LEDs
	Mechanical	Hot swap ejector handle
Software Support	Operating System	None
Conformal Coating		Humiseal 1A33 Polyurethane (Optional) Humiseal 1B31 Acrylic (Optional)
	Other	
MTBF	MIL Hand book 217-F @ TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	
Trademarks and Disclaimer	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice	