

# Specifications

Architecture		
<b>Physical</b>	<b>Dimensions</b>	Single module (mid-size and full-size optional) Width: 2.89" (73.5 mm) Depth 7.11" (180.6 mm)
<b>Type</b>	<b>AMC Ethernet</b>	GbE Dual Port Gb/s per Port
Standards		
<b>AMC</b>	<b>Type</b>	AMC.2
<b>Module Management</b>	<b>IPMI</b>	IPMI v2.0
	<b>Ports</b>	0 and 1
Configuration		
<b>Power</b>	<b>AMC213</b>	3 W
<b>Environmental</b>	<b>Temperature</b>	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 200 LFM). See <a href="#">environmental spec sheet</a> Storage Temperature: -40° to +90°C
	<b>Vibration</b>	1G, 5 to 500 Hz on each axis
	<b>Shock</b>	30Gs on each axis
	<b>Relative Humidity</b>	5 to 95% non-condensing
<b>Front Panel</b>	<b>Interface Connectors</b>	Dual RJ-45 Micro USB
	<b>LEDs</b>	IPMI management control Activity, Link
	<b>Mechanical</b>	Hot swap ejector handle
<b>Software Support</b>	<b>Operating System</b>	Independent
Other		
<b>MTBF</b>	MIL Hand book 217-F@ TBD hrs	
<b>Certifications</b>	Designed to meet FCC, CE and UL certifications, where applicable	
<b>Standards</b>	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
<b>Warranty</b>	Two (2) years	

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.