

## Architecture

Physical	Dimensions	Mid-Height (Full-Height option) Width: 2.89 in. (73.5 mm) Depth: 7.11 in. (180.6 mm)
Type	AMC GbE	Six port of GbE

## Standards

AMC	Type	AMC.1 and AMC.2
Module Management	IPMI	IPMI Version 2.0
PCIe	Lanes	x4

## Configuration

Power	AMC222	~25W (CPU Dependent)
	Temperature	Operating Temperature: 0° to 60° C Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
	Interface Connectors	Quad SFP with dual micro USB for USB and Serial
Front Panel	LEDs	IPMI Management Control Activity/Link and two user defined
	Mechanical	Hot Swap Ejector Handle
Software Support	Operating Systems	Linux, Windows, Solaris and VxWorks

## Other

MTBF	MIL Spec 217-F >TBD
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.