

SPECIFICATIONS

Architecture		
Physical	Dimensions	Width: 2.89" (73.5 mm)
		Depth 7.11" (180.6 mm)
		Single module, mid-size (full-size options available)
Type	AMC Wireless Access	IEEE 802.11b; 802.11g and 802.11n
Standards		
AMC	Type	AMC.0 and AMC.2
Module Management	IPMI	IPMI version 2.0
Configuration		
Power	AMC227	5W
Environmental	Temperature	Operating temperature: -5° to 45°C (55°C for limited time, performance restrictions may apply), (See environmental spec sheet)
		Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500Hz on each axis
	Shock	Operating 30Gs each axis
	Relative Humidity	5 to 95 per cent, non-condensing
Front Panel	Interface Connectors	GbE via dual SFP
		SMA for Wi-Fi Antennae
		IPMI RS-232 via micro USB
	LEDs	IPMI management control
		Activity / Link / Status LEDs
Mechanical	Hot swap ejector handle	
Software Support	Operating System	Independent
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	
Trademarks and Disclaimer	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice	