

## Architecture

Physical	Dimensions	Single-Width, Full-Height
		Width: 2.89 in. (73.5 mm)
		Depth: 7.11 in. (180.6 mm)
Type	AMC Ethernet	10GbE switch
		13 ports
		10GbE per port

## Standards

AMC	Type	AMC.2
Module Management	IPMI	IPMI Version 2.0
10GBASE-KR	Ports	0, 1, 4, 8 and 17

## Configuration

Power	AMC229	20W
	Temperature	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 200 LFM)
		Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
	Interface Connectors	SFP+
Front Panel	LEDs	IPMI Management Control
		Signal Detect
	Mechanical	Hot Swap Ejector Handle
Software Support	Operating Systems	Independent

## Other

MTBF	MIL Handbook 217-F > TBD Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years.
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.