

Architecture

Physical	Dimensions	Single-Width, Half-Height (with Mid or Full Height options)
		Width: 2.89 in. (73.5 mm)
Type	AMC Serial 16 Ports	Depth: 7.11 in. (180.6 mm)
		RS-422/485
		Sixteen Ports with no hardware handshake

Standards

AMC	Type	AMC.1
Module Management	IPMI	IPMI Version 2.0
PCIe	Lanes	x4

Configuration

Power	AMC321	4W
ESD	Human Model	Up to ±15 kV
	Temperature	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 200 LFM)
Environmental		Storage Temperature: -40° to +90° C
	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel	Interface Connectors (See Ordering Options)	High-density SCSI type connector Micro 68-Pin SCSI to (16) DB9 Male connectors
	LEDs	IPMI Management Control Activity
	Mechanical	Hot Swap Ejector Handle
Software Support	Operating Systems	Linux, Windows, Solaris and VxWorks

Other

MTBF	MIL Spec 217-F@ 160,000 Hrs.
Certifications	Design to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years.
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.