

Architecture		
Physical	Dimensions	Single-Width, Mid-Height (with Full-Height option)
		Width: 2.89 in. (73.5 mm) Depth: 7.11 in. (180.6 mm)
Type	AMC Video	5 Link DVI (HDMI) and one DVI-I Video
	Hex Ports	Hex ports using break out Adapter Cable
	Video Resolution	Connection for 480p, 720p, and 1080i and 1080p
	Memory	1 GB of GDDR3 memory
Standards		
AMC	Type	AMC.1 PCIe Gen2
Module Management	IPMI	IPMI Version 2.0
PCIe	Lanes	x4 or x8
Configuration		
Power	AMC343	30W
	Temperature	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 200 LFM), Conduction cooled unit does not need any air flow Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
	Interface Connector	High density connector
Front Panel	Adapter	HDC to Hex Link DVI
	LEDs	IPMI Management Control
	Mechanical	Hot Swap Ejector Handle
Software Support	Operating Systems	Linux, Windows and Solaris
Other		
MTBF	MIL Handbook 217-F TBD Hrs.	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years	
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.	