

## SPECIFICATIONS

Architecture		
Physical	Dimensions	Width: 2.89" (73.5 mm)
		Depth 7.11" (180.6 mm)
Type	AMC Video	DVI or VGA Video Adapter
	Dual Ports	Dual ports using "Y" Adapter Cable, either DVI or VGA (see ordering options)
	Video Resolution	Screen resolutions up to 1920x1080
	Memory	16 MB of memory
Standards		
AMC	Type	AMC.1
Module Management	IPMI	IPMI v2.0
PCIe	Lanes	x1
Configuration		
Power	AMC348	3 W
Environmental	Temperature	See ordering options and <a href="#">environmental spec sheet</a>
		Storage Temperature: -40° to +85°C
	Vibration	1 G, 5-500 Hz each axis
	Shock	30 Gs each axis
Front Panel	Relative Humidity	5 to 95% non-condensing
	Interface Connectors	Low Force Helix (LFH) connector
	Adapter	LFH to two DVI-I or LFH to two standard HD15 connectors (see notes)
	LEDs	IPMI Management Control
Software Support	Mechanical	Hot Swap Ejector Handle
	Operating Systems	Linux and Windows
Other		
MTBF	MIL Spec 217-F TBD Hrs.	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	