

Architecture		
Physical	Dimensions	Single-Width, Mid-Height (with Full-Height option)
		Width: 2.89 in. (73.5 mm)
Type	AMC Video Single Ports Video Resolution Memory	Depth: 7.11 in. (180.6 mm)
		DVI-I
		DVI-I connector provides both the DVI as well as the VGA output
		Screen resolutions up to 1920x1440
		16 MB of DDR memory
Standards		
AMC	Type	AMC.1
Module Management	IPMI	IPMI Version 2.0
PCIe	Lanes	x1
Configuration		
Power	AMC349	4W
	Temperature	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 200 LFM), Conduction cooled unit does not need any air flow
Environmental	Vibration Shock Relative Humidity Interface Connector	Storage Temperature: -40° to +90° C
		1G, 5-500Hz each axis
		30Gs each axis
		5 to 95 percent, non-condensing
Front Panel	LEDs	DVI-I
	Mechanical	IPMI Management Control
Software Support	Operating Systems	Hot Swap Ejector Handle
		Linux, Windows, Solaris
Other		
MTBF	MIL Spec 217-F TBD Hrs.	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years	
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.	
Notes	<ol style="list-style-type: none"> 1. LFH to two DVI-I connectors "Y" adapter cable for digital displays can be ordered separately. 2. LFH to two standard HD15 connectors "Y" adapter cable for use with analog displays can be ordered separately. 	