



AMC521 – 24 Channels ADC, Mixed Sampling Rate, 16-Bit



KEY FEATURES

- Sixteen channel of TI ADS42JB69 ADC 16-bit @ 250 MSPS
- Eight channel SAR TI ADS8568 ADC 16-bit @ 650 KSPS simultaneous
- Interface to the FPGA via JESD204B
- 24 LVDS for Clock/Trig and/or GPIO
- Virtex-7 FPGA 415T or 690T in FFG1158
- Internal/External clock
- Clock Jitter Cleaner with Dual Loop PLLs
- Trig In/Out
- A/D input via SSMC connectors

AdvancedMC™

Benefits of Choosing VadaTech

- Low Jitter Clock distribution via an M-LVDS Cross Bar Switch
- Backplane TCLKA, TCLKB, TCLKC, TCLKD, and FCKLA
- Onboard VCXO
- Design utilizes proven VadaTech subcomponents and engineering techniques
- Electrical, mechanical, software, and system-level expertise in house
- Full ecosystem of front and rear boards, enclosures, specialty modules, and test/dev products from one source
- AS9100 and ISO9001 certified company

The AMC521 utilizes eight dual channel ADS42JB69 ADC converters at 250 MSPS with 16bit resolution for 16 high sampling rate channels. In addition the module has eight 16-bit Successive Approximation Register (SAR) based on TI ADS8568 ADC at a lower sampling rate for measurements up to 650 KSPS. There are also 24 LVDS I/O which can be used for Clock In/Out, Trig In/Out or GPIO.

The unit has an M-LVDS Cross Bar Switch (CBS) for clock distribution which allows clocking from front panel, backplane, or onboard VCXO. The clock outputs to the backplane for distribution to other modules. The AMC521 has a Virtex-7 FPGA with option of 415T or 690T in FFG1158 package.

The AMC Ports 4-7 and 8-11 are routed to the FPGA for PCIe, XAUI, SRIO, or other SerDes protocols. AMC Ports 0, 1 and 2, 3 are also routed to the FPGA for base channel and storage point-to-point connectivity.

This VadaTech Product can be incorporated into High Energy Physics architecture.

CLOCK JITTER CLEANER

The clock to the ADC has an Ultra-Low RMS Jitter Cleaner with Dual Loop PLLs, with 88 fs RMS jitter (12 KHz to 20 MHz) and 162.5 dBc/Hz noise floor at 245.76 MHz.

BLOCK DIAGRAM



FRONT PANEL



Doc No. 4FM737-12 Rev 01



Version 3.3 – FEB/20

info@vadatech.com

SPECIFICATIONS

Architecture			
Physical	Dimensions	Double module, Full-size	
		Width 5.85" (148.5 mm)	
		Depth 7.11" (180.6 mm)	
Туре	AMC FPGA	24 ADC (16 fast and 8 slower sampling rate) @ 16-bit	
Standards			
MTCA	Туре	MTCA.0, MTCA.1	
AMC	Туре	AMC.0, AMC.1, AMC.2, AMC.3, AMC.4	
Module Management	IPMI	IPMI v2.0	
PCle	Lanes	Dual x4 or single x8 via FPGA to AMC	
SRIO	Lanes	Dual x4 via FPGA to AMC	
Ethernet	Lanes	Dual 10GbE via FPGA and dual GbE via FPGA	
Configuration			
Power	AMC521	~25W, application specific (up to 50W)	
Environmental	Temperature	Operating Temperature: -5° to 55°C (air flow requirements >400 LFM)	
		(See <u>environmental spec sheet</u>))	
		Storage Temperature: -40° to +85°C	
	Vibration	1G, 5 to 500 Hz on each axis	
	Shock	30Gs each axis	
	Relative Humidity	5 to 95% non-condensing	
Front Panel	Interface Connectors	FPGA JTAG Port	
		24 I/O via DensiShield connectors	
		ADC inputs via SSMC connectors	
		IPMI RS-232	
	LEDs	IPMI Management Control	
		Four user defined LED	
	Mechanical	Hot-Swap Ejector Handle	
Software Support	Operating Systems	Independent	
Other			
MTBF	MIL Hand book 217-F @ TBD Hrs		
Certifications	Designed to meet FCC, CE and UL certifications where applicable		
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards		
Warranty	Two (2) years, see VadaTech Terms and Conditions		

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA[™] and the AdvancedMC[™] logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

Doc No. 4FM737-12 Rev 01



Version 3.3 – FEB/20

info@vadatech.com

ORDERING OPTIONS

AMC521 - A0C - DEF - GHJ

A = ADC Channels 0 = 24 Channels 1 = 16 Channels (no SAR)	D = FPGA 1 = XC7V415T 2 = XC7V690T	G = Front Panel Type 0 = MicroTCA.0 1 = MicroTCA.1
	E = FPGA, Speed 1 = Low 2 = High 3 = Highest	H = Temperature Range 0 = Commercial (-5 to +55° C) 1 = Industrial (–20 to +70° C)
C = Front Panel 1 = Reserved 2 = Reserved 3 = Full-size 4 = Extended-size (8 HP)	F = PCle Option 0= No PCle 1= PCle on Ports 4-7 2 = PCle on Ports 8-11 3 = PCle on Ports 4-11	J = Conformal Coating 0 = No coating 1 = Humiseal 1A33 Polyuretha 2 = Humiseal 1B31 Acrylic

RELATED PRODUCTS



Doc No. 4FM737-12 Rev 01



Version 3.3 - FEB/20

Polyurethane Acrylic

info@vadatech.com