

Specifications

Architecture		
Physical	Dimensions	Single module, mid-size (full-size optional) Width: 2.89" (73.5 mm) Depth 7.11" (180.6 mm)
Type	AMC FPGA	Altera Stratix® IV EP4S100Gx
Memory		Three banks of QDR-II+ (18-bit wide)
Standards		
AMC	Type	AMC.1, AMC.2, AMC.3 and AMC.4 (FPGA programmable)
Module Management	IPMI	IPMI v2.0
PCIe	Lanes	x4 or x8
SRIO	Lanes	Dual x4
XAUI	Lanes	Dual Port XAUI
Ethernet	GbE and 10GbE	Dual 1000-BaseBX from PPC or FPGA
Configuration		
Power	AMC531	35W (FPGA size and application dependent)
Environmental	Temperature	See Ordering Options and Environmental Spec Sheet Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock	30G each axis
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	Dual SFP+ and RJ-45 Micro USB for MGT RS-232 and CPU RS-232
	LEDs	IPMI management control Activity/Link user LEDs
	Mechanical	Hot-swap ejector handle
Software Support	Operating System	Linux, VxWorks
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty		Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.