

Specifications

Architecture		
Physical	Dimensions	Single module, mid-size (full-size and Extended -size optional) Width: 2.89" (73.5 mm) Depth 7.11" (180.6 mm)
Type	AMC FPGA	Xilinx Virtex UltraScale™ XCVU440 FPGA Single bank of DDR4 (64-bit wide)
Standards		
AMC	Type	AMC.1, AMC.2 and AMC.4 (FPGA programmable)
Module Management	IPMI	IPMI v2.0
PCle	Lanes	Dual x4 or single x8 via FPGA to AMC
SRIO/Aurora	Lanes	Dual x4 via FPGA to AMC
Ethernet	1/10/40GbE	Dual 1/10/40GbE via FPGA (Ports 0-1, 4-11) and/or Dual 1000-BaseBX from PPC to Ports 0-1
Configuration		
Power	AMC596	~65W (application specific)
Environmental	Temperature	See Ordering Options and Environmental Spec Sheet Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz
	Shock	30Gs on each axis
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	Micro USB for MGT RS-232 and CPU RS-232
	LEDs	IPMI Management Control 4 user defined LEDs
	Mechanical	Hot swap ejector handle
Software Support	Operating System	Linux, VxWorks and Windows
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.