

## SPECIFICATIONS

Architecture		
Physical	Dimensions	Single module, mid-size (full-size option available)
		Width: 2.89" (73.5 mm)
		Depth: 7.11" (180.6 mm)
Type	AMC Storage	1.8" Serial ATA drive
		Optional Solid State Drive (SSD) – contact sales for availability and capacity
		SATA transfer rate of 6 Gbps
Standards		
AMC	Type	AMC.1
Module Management	IPMI	IPMI v2.0
PCIe	Lanes	x2 PCIe Gen 2 lanes
Configuration		
Power	AMC622	2 W without the drive
Environmental	Temperature	Operating temperature: -5° to 55° C (air flow requirement of >100 LFM), industrial and military versions also available (See <a href="#">environmental spec sheet</a> )
		Storage temperature: -40° to +70° C with the disk
	Vibration	SSD/Rotary disk dependent
	Shock	SSD/Rotary disk dependent
Front Panel	Relative Humidity	5 to 95 percent, non-condensing
	LEDs	IPMI management control
		Activity
		Mechanical
Software Support	Operating System	Linux, Windows, Solaris and VxWorks
Other		
MTFB	MIL Handbook 217-F@TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Compliance	RoHS and NEBS.	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	
Trademarks and Disclaimer	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice	