

AMC630 – 1.8" Quad SATA Drive RAID HBA

1.8" Quad SATA Drive, HBA



KEY FEATURES

- 1.8" SATA 6.0 Gbps drive HBA (Host Bus Adapter)
- AMC.1 x2 PCIe Gen 2
- Four SATA disks on a single AMC
- Independent disk or hardware RAID 0, 1, and 10
- Double-module, compact-size (mid and full-size options available)
- IPMI 2.0 compliant
- RoHS compliant

AdvancedMC™

Benefits of Choosing VadaTech

- 6 Gbps SATA drive provides twice the front-end transfer rate as the previous generation of VadaTech modules
- Removable disk drives, front drives can be removed without removing the AMC
- Design utilizes proven VadaTech subcomponents and engineering techniques
- Electrical, mechanical, software, and system-level expertise in house
- AS9100 and ISO9001 certified company

The AMC630 is VadaTech second generation storage product for a 1.8" SATA disk drive in a double module, compact-size (mid or full-size optional) AdvancedMC™ (AMC) form factor based on the AMC.1 specification. Drives can be SSD or rotary with 6 Gbps SATA.

The module also supports an independent disk or integrated RAID 0, 1 and 10. The front SATA drives are swappable without removing the AMC from the chassis. The rear (3rd and 4th) SATA drives are latched down with screwed braces. They can be removed with some light disassembly of the AMC.

BLOCK DIAGRAM




Figure 1: Block Diagram

FRONT PANEL




Figure 2: Front Panel

SPECIFICATIONS

Architecture		
Physical	Dimensions	Double module, compact-size (mid-size and full-size options available) Width: 5.85" (148.5 mm) Depth: 7.11" (180.6 mm)
	Type	AMC Storage 1.8" Serial ATA drive Optional Solid State Drive (SSD) – contact sales for availability and capacity SATA transfer rate of 6 Gbps
Standards		
AMC	Type	AMC.1
Module Management	IPMI	IPMI v2.0
PCIe	Lanes	x2 PCIe Gen 2 lanes
Configuration		
Power	AMC630	2 W without the drive
Environmental	Temperature	Operating temperature: -5° to 55° C (air flow requirement of >100 LFM), industrial and military versions also available (See environmental spec sheet) Storage temperature: -40° to +70° C with the disk
	Vibration	SSD/Rotary disk dependent
	Shock	SSD/Rotary disk dependent
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel	LEDs	IPMI management control
		Activity
	Mechanical	Hot swap ejector handle
Other		
MTBF	MIL Handbook 217-F@TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Compliance	RoHS and NEBS.	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and μ TCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

AMC630 – 1.8” Quad SATA Drive RAID HBA

ORDERING OPTIONS

AMC630 – ABC – DE0 – 0HJ

A = First SATA Drive Capacity*

0 = None
1 = 240 GB SSD
2 = 360 GB SSD
3 = 480 GB SSD
4 = 1 TB SSD
5 = Reserved

B = Second SATA Drive Capacity*

0 = None
1 = 240 GB SSD
2 = 360 GB SSD
3 = 480 GB SSD
4 = 1 TB SSD
5 = Reserved

C = Front Panel Size

1 = Compact-size
2 = Mid-size
3 = Full-size

D = Third SATA Drive Capacity*

0 = None
1 = 240 GB SSD
2 = 360 GB SSD
3 = 480 GB SSD
4 = 1 TB SSD
5 = Reserved

E = Forth SATA Drive Capacity*

0 = None
1 = 240 GB SSD
2 = 360 GB SSD
3 = 480 GB SSD
4 = 1 TB SSD
5 = Reserved

H = Temperature Range**

0 = Commercial (-5 to +55° C)
1 = Industrial (-20 to +70° C)
2 = Military (-40 to +85° C)***

J = Conformal Coating

0 = None
1 = Humiseal 1A33 Polyurethane
2 = Humiseal 1B31 Acrylic

* Contact sales for availability and size of larger drives

** SSD option is required for Industrial or Military grade

*** Edge of module for conduction-cooled boards

RELATED PRODUCTS



EXP100 1U Express
Development Platform



UTC002 MCH



UTC020 Power Module

CONTACT US

VadaTech Corporate Office

198 N. Gibson Rd.
Henderson, NV 89014
Email: info@vadatech.com
Telephone: +1 702 896-3337
Fax: +1 702 896-0332

Asia Pacific Sales Office

7th Floor, No. 2, Wenhui Street, Neihu District, Taipei
City, Taiwan 11445
Email: info@vadatech.com
Telephone: +886-2-2627-7655
Fax: +886-2-2627-7792

VadaTech European Sales Office

Ocean Village Innovation Centre, Ocean Way,
Ocean Village, Southampton, SO14 3JZ
Email: info@vadatech.com
Telephone: +44 2380 381982
Fax: +44 2380 381983