

AMC705

Processor AMC, Layerscape
LX2160A, SRIO/PCIe



AMC705

Key Features

- Processor AMC with Layerscape LX2160A
- Two banks of 64-bit DDR4 memory (16 GB total)
- Ports 4-7 selectable between SRIO and PCIe
- Ports 8-11 option for PCIe x4 (or single x8 ports 4-11)
- 100GbE/40GbE via QSFP28 or as Quad 10GbE
- GbE via RJ-45 and 10GbE/GbE ports 0 and 1
- 64Gb Flash
- SDHC socket
- 16 cores at up to 2.2 GHz
- Single-module, full-size per AMC.0
- RoHS Compliant

Benefits

- 16 ARM Cortex-A72 CPU cores, running up to 2.2 GHz
- 8 MB cache/on-chip memory
- Design utilizes proven VadaTech subcomponents and engineering techniques
- Electrical, mechanical, software, and system-level expertise in house
- Full system supply from industry leader
- AS9100 and ISO9001 certified company



vadatech
THE POWER OF VISION

AdvancedMC™



AMC705

The AMC705 is a Processor AMC (PrAMC) based on the NXP Layerscape LX2160A in a single-module, full-size AMC form factor based on the AMC.1, AMC.2 and the AMC.4 specifications. The LX2160A provides 16 Cortex-A72 cores with 8 MB platform cache and dual 64-bit memory controllers.

The front panel provides GbE via RJ-45 connector and 100GbE/40GbE/Quad-10GbE via QSFP28 connector.

The AMC705 provides dual 10/1GbE to the rear per AMC.2 specification on Ports 0 and 1. Ports 0 and 1 will support 10G operation but this is outside the AMC standard (MCH with 10G on ports 0/1 or point to point on backplane is required). The 10GbE support on ports 0 and 1 allows only 40GbE on the front panel. If 100GbE is desired ports 0 and 1 must run at 1GbE.


Ports 4-7 can be configured as SRIO or PCIe. The module has option for PCIe on port 8-11. When ports 8-11 are routed, the module could be configured as dual PCIe x4 or single x8.

Two 64-bit wide memory banks provide up to 16 GB of DDR4 with ECC.



Figure 1: AMC705

Front Panel



Specifications

Architecture		
Physical	Dimensions	Single module, full-size
		Width: 2.89" (73.5 mm)
		Depth 7.11" (180.6 mm)
Type	PrAMC	NXP Layerscape LX2160A
Standards		
AMC	Type	AMC.0, AMC.1, AMC.2 and AMC.4
Module Management	IPMI	IPMI v2.0
SRIO 2.0 / PCIe	Lanes	x4 SRIO also option for dual PCIe x4 or single x8 PCIe
40GbE	Lanes	100G/40GbE via front panel
Ethernet	GbE	GbE/10GbE on Ports 0-1, single GbE via front panel
Configuration		
Power	AMC705	~35W
Environmental	Temperature	See Ordering Options and Environmental Spec Sheet
		Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock	Operating 325 G/2 ms, 160G/1 ms
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	100G/40GbE via QSFP28 or as Quad 10GbE
		GbE via RJ-45
		Dual RS-232 management ports via micro USB
	LEDs	IPMI Management Control
		Link/Activity
	Mechanical	Hot-swap ejector handle
Software Support	Operating System	Linux (consult Sales for other OS options)
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty	Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Ordering Options

AMC705 – ABC-DEF-00J

A = Processor Option 0 = Reserved 1 = Reserved 2 = LX2160A, 2.2 GHz with SE	D = PORTS 8-11 0 = No connect 1 = PCIe	
B = Ports 0/1 and QSFP28 Configuration 0 = GbE/40GbE 1 = 10GbE/40GbE 2 = GbE/Quad 10GbE 3 = 10GbE/Quad 10GbE 4 = GbE/100GbE 5 = Reserved	E = QSFP28 TXCVR** 0 = None 1 = SR 2 = LR 3 = Reserved	
C = Front Panel 1 = Reserved 2 = Reserved 3 = Full-size 4 = Reserved 5 = Reserved 6 = Full-size, MTCA.1 (captive screws)		J = Temperature Range and Coating 0 = Commercial (–5° to +55°C), No coating 1 = Commercial (–5° to +55°C), Humiseal 1A33 Polyurethane 2 = Commercial (–5° to +55°C), Humiseal 1B31 Acrylic 3 = Industrial (–20° to +70°C), No coating 4 = Industrial (–20° to +70°C), Humiseal 1A33 Polyurethane 5 = Industrial (–20° to +70°C), Humiseal 1B31 Acrylic 6 = Extended (–40° to +85°C), Humiseal 1A33 Polyurethane* 7 = Extended (–40° to +85°C), Humiseal 1B31 Acrylic*

Notes: *Conduction cooled; temperature is at edge of module. Consult factory for availability.

** Option B drives the TXCVR speed at 40GbE or 100GbE (if configured as quad 10GbE, B=2 or B=3, the TXCVR is 40GbE)

Related Products

AMC725



- Intel® Xeon E3 processor options with PCH
- DVI graphics (SM750 w/16 MB DDR), up to 1920x1440 resolution
- Optional up to 256 GB SSD with RAID option

VT811



- MTCA System Platform 19" x 8U x 14.9" deep (with handles 16.23" deep)
- Full redundancy with dual MicroTCA Carrier Hub (MCH), dual Cooling Units and quad Power Modules
- Up to twelve AMCs: 12 front mid-size double module slots and RTM slots

VT814



- MicroTCA rack mount or desktop chassis platform, 19" x 2U x 14.2" deep
- Compliant to MTCA.4 specifications with rear IO for High-Energy Physics and other applications
- Supports up to six MTCA.4 mid-size, double module AMCs and RTMs

Contact

VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014

Phone: +1 702 896-3337 | Fax: +1 702 896-0332

Asia Pacific Sales Office

7 Floor, No. 2, Wenhua Street, Neihu District, Taipei 114, Taiwan

Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR

Phone: +44 2380 016403

info@vadatech.com | www.vadatech.com

Choose VadaTech

We are technology leaders

- First-to-market silicon
- Constant innovation
- Open systems expertise

We commit to our customers

- Partnerships power innovation
- Collaborative approach
- Mutual success

We deliver complexity

- Complete signal chain
- System management
- Configurable solutions

We manufacture in-house

- Agile production
- Accelerated deployment
- AS9100 accredited



Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

