

## SPECIFICATIONS

Architecture		
Physical	Dimensions	Single module, mid-size (full-size optional) Width: 2.89" (73.5 mm) Depth 7.11" (180.6 mm)
	Type	AMC Processor Intel® Xeon™ with up to four core at 2.0 GHz and 8 MB LLC
Standards		
AMC	Type	AMC.0, AMC.1, AMC.2 and/or AMC.3
Module Management	IPMI	IPMI version 2.0
PCIe	Lanes	PCIe on ports 4-7 and XAUI on ports 8-11
Configuration		
Power	AMC723	18W to 58W (CPU dependant)
Environmental	Temperature	Operating temperature: -5° to 55° C (air flow requirement of >600 LFM), industrial and military versions also available (See <a href="#">environmental spec sheet</a> ) Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s <sup>2</sup> (1G), 5 to 500Hz on each axis
	Shock	Operating 325G / 2 ms, 160G / 1 ms
	Relative Humidity	5 to 95 per cent, non-condensing
Front Panel	Interface Connectors	Dual GbE via RJ-45
		Dual USB via mini USB
		Dual RS-232 via micro USB
	LEDs	IPMI management control Activity / Link user LEDs
	Mechanical	Hot swap ejector handle
Software Support	Operating System	Linux, VxWorks and Windows
Conformal Coating		Humiseal 1A33 Polyurethane (Optional) Humiseal 1B31 Acrylic (Optional)
	Other	
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years
Trademarks and Disclaimer		The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice