

## SPECIFICATIONS

Architecture		
Physical	Dimensions	Double module, full-size
		Width 5.85 in. (148.5 mm)
		Depth 7.11 in. (180.6 mm)
Type	AMC	AMC 100 GbE Ethernet
Standards		
AMC	Type	AMC.1, AMC.2 and AMC.4
Power	AMC738	82W
Environmental	Temperature	Operating temperature: -5° to 55° C (air flow requirement of >200 LFM, industrial and military versions also available (See <a href="#">environmental spec sheet</a> )
		Storage Temperature: -40° to +85° C
	Altitude	Chassis Dependent
	Relative Humidity	5 to 95 percent, non-condensing
	Mechanical	Hot-swap extractor handle
Conformal Coating	LEDs	IPMI management, Activity, GPIO
		Humiseal 1A33 Polyurethane (Optional) Humiseal 1B31 Acrylic (Optional)
Other		
MTBF	MIL Hand book 217-F @ TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	
Trademarks and Disclaimer	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice	