

# Specifications

Architecture	
<b>Physical</b>	<b>Dimensions</b> Width: 2.89" (73.5 mm) Depth: 7.11" (180.6 mm)
<b>Type</b>	<b>AMC Processor</b> Intel® Xeon® Processor E-2176M AMC
Standards	
<b>AMC</b>	<b>Type</b> AMC.0, AMC.2 and/or AMC.3
<b>Module Management</b>	<b>IPMI</b> IPMI v2.0
<b>10/40GbE</b>	<b>Lanes</b> Dual XAUI or dual 40GBase-KR4
Configuration	
<b>Power</b>	<b>AMC761</b> ~58W
<b>Environmental</b>	<b>Temperature</b> See <a href="#">Ordering Options</a> and <a href="#">Environmental Spec Sheet</a> Storage Temperature: -40° to +90°C <b>Altitude</b> Chassis dependent <b>Relative Humidity</b> 5 to 95% non-condensing
<b>Front Panel</b>	<b>Interface Connectors</b> 1x RJ-45 for GbE 2x USB type C connectors for USB 3.0 2x Micro USB for IPMI RS-232 and PCH RS-232 1x Mini Display Port for graphics <b>LEDs</b> IPMI, activity and user defined <b>Mechanical</b> Hot-swap ejector handle
<b>Software Support</b>	<b>Operating System</b> Linux (consult VadaTech for other options)
Other	
<b>MTBF</b>	MIL Hand book 217-F@ TBD hrs
<b>Certifications</b>	Designed to meet FCC, CE and UL certifications, where applicable
<b>Standards</b>	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
<b>Warranty</b>	Two (2) years, see <a href="#">VadaTech Terms and Conditions</a>

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.