

## Architecture

Physical	Dimensions	Mid-Height (Full-Height option) Width: 2.89 in. (73.5 mm) Depth: 7.11 in. (180.6 mm)
Product	Video Driver	Dual RGB to dual RGB

## Standards

AMC Module Management	Type IPMI	AMC.0 IPMI Version 2.0
-----------------------	-----------	---------------------------

## Configuration

Power	AMC901 Temperature	<2W Operating Temperature: 0° to 65° C Storage Temperature: -40° to +90° C
Environmental	Vibration Shock Relative Humidity	1G, 5-500Hz each axis 30Gs each axis 5 to 95 percent, non-condensing
Interface Connectors Conformal Coating	Rear	Dual Micro DB-15 Humiseal 1A33 Polyurethane Conformal Coating Humiseal 1B31 Acrylic Conformal Coating

## Other

MTBF	MIL Hand Book 217-F > 391,000 Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS
Warranty	Two (2) years
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.