

Specifications

Architecture		
Physical	Dimensions	Single module, mid-size (full-size option available) Width: 2.89" (73.5 mm) Depth 7.11" (180.6 mm)
Type	AMC Analog	Triple Sine wave clock output
Configuration		
Power	AMC903	20W at start up and after warm up 10W
Environmental	Temperature	See ordering options Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock	Operating 30G on each axis
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	3x SSMC and 1x micro USB
	LEDs	Status
	Mechanical	Hot swap ejector handle
Software Support	Operating System	N/A
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.