

Specifications

Architecture	
Physical	Dimensions Single or double module. Compact, mid, full and extended-size Width: Width 2.89" (73.5 mm) for single module, 5.85" (148.5 mm) for double module Depth: 7.11" (180.6 mm) for single or double module
Type	Filler Panel To prevent air flow through the front of the chassis
Standards	
AMC	Type AMC.0
MTCA	Type MTCA.0 and MTCA.1
Configuration	
Power	AMC999 0W
Environmental	Temperature Operating temperature: -50° to 85°C Storage Temperature: -70° to +95°C
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.