

## Architecture

Physical	Dimensions	Width: 12.687in. (322.25 mm) Depth: 3.701 in. (94.00 mm)
Type	Rear Transition	Expansion

## Standards

ATCA	<b>Type</b>	ATCA Rear Transition
------	-------------	----------------------

## Configuration

Power	ART103 Temperature	4W Operating Temperature: 0° to 65° C Storage Temperature: -40° to +90° C
Environmental	Vibration Shock	1G, 5-500Hz each axis 30Gs each axis
Expansion	Relative Humidity PCIe	5 to 95 percent, non-condensing Expansion to another ART103 or to an ATC103, ATC104, ATC105, ATC106, ATC107, ATC108, ATC109, AMC103 or PCI103 One SCSI type connector for the PMC J4 user I/O Two InfiniBand type connectors for PCIe x4 copper expansion
Rear Panel	Interface Connectors	One 10/100Mbit RJ-45 connector Two Gigabit Ethernet RJ-45 connectors One Serial RS-232 RJ-45 connector x4 PCIe expansion via fiber
	LEDs	Link and Activity PCIe Lane Good
	Mechanical	Hot Swap Ejector Handle

## Other

MTBF	MIL Spec 217-F@ 495,000 Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.