

Architecture

| | | |
|----------|-----------------|---|
| Physical | Dimensions | Width: 12.687in. (322.25 mm) Depth: 3.701 in. (94.00 mm) |
| Type | Rear Transition | GbE Switch |

Standards

| | | |
|------|-------------|----------------------|
| ATCA | Type | ATCA Rear Transition |
|------|-------------|----------------------|

Configuration

| | | |
|---------------|----------------------|---|
| Power | ART110 | 20W |
| | Temperature | Operating Temperature: 0° to 65° C Storage Temperature: -40° to +90° C |
| Environmental | Vibration | 1G, 5-500Hz each axis |
| | Shock | 30Gs each axis |
| | Relative Humidity | 5 to 95 percent, non-condensing |
| | | 12 SFP |
| | Interface Connectors | One 10/100/1000 GbE RJ-45 (Host) One Serial RS-232 RJ-45 (Host) |
| Rear Panel | | One Serial RS-232 RJ-45 (GbE Management) |
| | LEDs | Link and Activity per GbE port IPMI Management |
| | Mechanical | Hot Swap Ejector Handle |

Other

| | |
|----------------------|---|
| MTBF | MIL Spec 217-F @ TBD Hrs. |
| Certifications | Designed to meet FCC, CE and UL certifications where applicable |
| Standards | VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards |
| Compliance | RoHS and NEBS |
| Warranty | Two (2) years |
| Trademarks and Logos | The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice. |