

Architecture		
Physical	Dimensions	Width: 12.687in. (322.25 mm) Depth: 3.701 in. (94.00 mm)
Type	Rear Transition	I/O Expansion
Standards		
ATCA	Type	ATCA Rear Transition
Configuration		
Power	ART113 Temperature	typical 16 W, 20W MAX Operating Temperature: 0° to 65° C Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
Rear Panel	Interface Connectors	RS-232 (DB-9) Dual 1000 GbE (RJ-45 for copper, LC style for Fiber) Triple USB (Type A receptacles) VGA (DB-15) Dual RS-232 via Micro DB-9
		Management LAN (RJ-45) LNK/ACT per GbE port
		IPMI Management SAS ACT/FLT
		LAN Management LNK/ACT
	LEDs	
	Mechanical	Hot Swap Ejector Handle
	Other	
MTBF	MIL Spec 217-F @ TBD Hrs.	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years	
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.	