

Specifications

Architecture		
Physical	Dimensions	Weight: 0.8 lbs (362.87 g)
		Width: 12.69" (322.25 mm)
		Depth: 3.7" (94 mm)
Type	ATCA RTM	Storage module for the VadaTech ATC129A
Standards		
PICMG	ATCA	PICMG 3.0 revision 2.0
Module Management	IPMI	IPMI version 2.0
Configuration		
Power	ART129A	~10 W
Environmental	Temperature	Operating temperature: -5° to 55° C (65°C for limited time, performance restrictions may apply), industrial and extended versions also available (See environmental spec sheet)
		Storage Temperature: -40° to +90°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500Hz on each axis
	Shock	Operating 30G on each axis
	Relative Humidity	5 to 95 per cent, non-condensing
Front Panel	Interface Connectors	Dual USB 2.0
		Dual removal SATA Storage
	Mechanical	Hot swap ejector handle
Software Support	Operating System	Agnostic
Conformal Coating		Humiseal 1A33 Polyurethane (Optional)
		Humiseal 1B31 Acrylic (Optional)
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and μ TCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.