

Specifications

Architecture			
Physical	Dimensions	Width: 12.69" (322.25 mm)	
		Depth: 3.7" (94 mm)	
		Weight: TBD	
Type	ATCA RTM	Rear I/O module for ATC130	
Standards			
PICMG	ATCA	PICMG 3.0 revision 2.0	
Module Management	IPMI	IPMI v2.0	
Ethernet		Layer two Managed GbE	
Configuration			
Power	ART130A	~10W	
Environmental	Temperature	See Ordering Options	
		Storage Temperature: -40° to +90°C	
		Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
		Shock	Operating 30G on each axis
	Relative Humidity	5 to 95% non-condensing	
Front Panel	Interface Connectors	x2 SFP	
		x2 RJ-45	
		DSUB-26	
	LEDs	IPMI management control	
	Mechanical	Hot-swap ejector handle	
Software Support	Operating System	Agnostic	
Other			
MTBF		MIL Hand book 217-F@ TBD hrs	
Certifications		Designed to meet FCC, CE and UL certifications, where applicable	
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty		Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.