

## SPECIFICATIONS

Architecture		
Physical	Dimensions	Width 12.69" (322.25 mm)
		Depth 3.7" (94 mm)
Type	ATCA RTM	I/O module
Standards		
Module Management	IPMI	IPMI Version 2.0
Ethernet		GbE
PICMG	ATCA	PICMG 3.0 R2.0
Configuration		
Power	ART998	0 W
Environmental	Temperature	Operating Temperature: -40° to 85° C
		Storage Temperature: -45° to +90° C
	Vibration	1G, 5 to 500 Hz on each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
Rear I/O	GbE	Eight RJ-45 ports
	Mechanical	Hot Swap Ejector Handle
Other		
MTBF	MIL Hand book 217-F @ TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	

### INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and  $\mu$ TCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information

### Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.