

SPECIFICATIONS

Architecture		
Physical	Dimensions	8U x 280mm
Type	ATCA Test Infrastructure	ATCA Blade
Standards		
ATCA	Type	PICMG 3.0 R3.0
Configuration		
Power	ATC002	4 Watts
Environmental	Temperature	Operating Temperature: -5° to 55° C Storage Temperature: -40° to +85° C
	Vibration	1G, 5 to 500 Hz on each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel	Interface Connectors	Dual SFP+ Three RJ-45 from each Base channel as egress ports Dual RS-232
	LEDs	IPMI Management Control Link/Activity and Status
	Mechanical	Hot Swap Ejector Handle
Other		
MTBF	MIL Hand book 217-F @ TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	
Trademarks and Disclaimer	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice	

PANEL VIEW

