

SPECIFICATIONS

Architecture		
Physical	Dimensions	Width: 12.687" (322.25 mm) Depth: 11.024" (280 mm)
	Type	ATCA Carrier Dual Shelf Manager
Standards		
AMC	Type	AMC.1
Module Management	IPMI	IPMI version 2.0 and PICMG 3.0
PICMG	ATCA	PICMG 3.0 R2.0
Configuration		
Power	ATC139	~0 W for carrier (Consult the VT011 data sheet)
Environmental	Temperature	Operating Temperature: -5° to 65°C (Air flow requirements is to be greater than 200 LFM) Available in industrial temperature range Storage Temperature: -40° to +60°C
	Vibration	0.5 G RMS, 20 to 20000 Hz random (operating) 6 Gs RMS (non-operating)
	Shock	30 Gs on each axis
	Relative Humidity	5 to 95 per cent, non-condensing
Software Support	Operating System	None
Conformal Coating		Humiseal 1A33 Polyurethane (Optional) Humiseal 1B31 Acrylic (Optional)
	Other	
MTFB		MIL Handbook 217-F@TBD Hrs
Certifications		Designed to meet FCC, CE and UL certifications where applicable
Compliance		PICMG 3.0 Rev 3.0, RoHS 2.
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years
Trademarks and Disclaimer		The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice

