

## Architecture

Physical	Dimensions	Width: 12.687in. (322.25 mm) Depth: 11.024 in. (280 mm)
Type	ATCA Graphic	10 DP with USB 2.0

## Standards

PICMG	ATCA	PICMG 3.0 R2.0
Module Management	IPMI	IPMI Version 2.0

## Configuration

Power	ATC340 Temperature	15W Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 100 LFM) Storage Temperature: -40° to +90° C
Environmental	Vibration Shock Relative Humidity	1G, 5-500Hz each axis 30Gs each axis 5 to 95 percent, non-condensing
Front Panel	Interface Connectors LEDs	Ten DP Ports Five up-stream USB ports IPMI Management Control USB power
Software Support	Mechanical Operating Systems	Hot Swap Ejector Handle Independent

## Other

MTBF	MIL Handbook 217-F > TBD Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years.
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.