

SPECIFICATIONS

Architecture		
Physical	Dimensions	Width: 3.94" (100.07 mm)
		Depth 6.37" (161.79 mm)
		3U cPCI, 6U option available
Type	cPCI	DVI Adapter
	Six Ports	Six ports DVI-D (port one is DVI-I) with HDC in the front
	Video Resolution	Up to 1920x1200 @ 60 Hz
	Memory	1 GB GDDR-5
PCI-X	Speed	133 MHz
Standards		
Compact PCI	Type	cPCI
Module Management	IPMI	None
Configuration		
Power	CP341	18 W
Environmental	Temperature	Operating Temperature: 0° to 65°C (air flow greater than 300 LFM)
		Storage Temperature: -40° to +90°C
	Vibration	Operating 9.8 m/s ² , 1G, 5 to 500Hz on each axis
	Shock	Operating 30G on each axis
	Relative Humidity	5 to 95 per cent, non-condensing
Front Panel	Interface Connectors	HDC for video output HDC cable to six standard DVI (cable included)
	LEDs	PCIe lane good and power fail
	Mechanical	Hot swap ejector handle
Software Support	Operating System	Linux, VxWorks, Solaris and Windows
Other		
MTBF	MIL Handbook 217-F@TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Compliance	RoHS and NEBS	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	
Trademarks and Disclaimer	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice	