

Specifications

Architecture		
Physical	Dimensions	Single Module
		Width: 2.71" (69 mm) Depth: 3.011" (76.5 mm)
Type	FMC	Quad Port 10GbE Copper Single FMC slot
Standards		
FMC	Type	ANSI/VITA 57.1 – 2008
Configuration		
Power	FMC120	10W
Environmental	Temperature	Operating temperature: -40° to 85°C (air flow requirements >400 LFM) See Ordering Options
		Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz
	Shock	30Gs each axis
Front Panel	Relative Humidity	5 to 95% non-condensing
	Interface Connectors	Quad RJ-45 connectors
	LEDs	None
Other		
MTBF	MIL Handbook 217-F@TBD Hrs.	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty	Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.