

Specifications

Architecture	
Physical	Dimensions Single Module Width: 2.71" (69 mm) Depth: 3.01" (76.5 mm)
Type	FMC Digitizer and Serial IO
Standards	
FMC	Type ANSI/VITA 57.1
Configuration	
Power	FMC159 2W
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +85°C Altitude TBD Vibration TBD Shock TBD Relative Humidity 5 to 95% non-condensing
Front Panel	Interface Connectors RF High-Density Connector and I/O via High-Density Connector LEDs Status
Software Support	Operating System Agnostic
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.