FMC216

ADC 12-bit @ 2.6 GSPS and DAC 14-bit @ 5.6 GSPS, FMC



FMC216

Key Features

- ADC AD9625
 - 8 JESD204B lanes from the ADC is routed to the FMC
 - 12-bit at 2.6 GSPS
 - Wide full power bandwidth supports IF sampling of signals up to 2 GHz
- DAC AD9129
 - 14-bit at 5.6 GSPS
- FPGA Mezzanine Card (FMC) per VITA 57
- Excellent dynamic performance
- Front panel interface includes CLK In, Trig In and Trig Out

Benefits

- High dynamic range for versatility in video / broadcast requirements
- Ideal for Broadband communications systems, Wireless infrastructure, LTE, ATE, RADAR/Jamming
- Compatible with a broad range of Xilinx- and Alterabased FMC carriers from VadaTech and others
- Electrical, mechanical, software, and system-level expertise in house
- Full system supply from industry leader
- AS9100 and ISO9001 certified company





THE POWER OF VISION

Block Diagram

Mezzanine Expansion Connector

FMC (VITA-57)



Figure 2: Functional Block Diagram for Option A=1





SSMC Connectors

ANALOG IN

REF IN

TRIG_IN

TRIG_OUT

LEDs

Status

ANALOG OUT

FMC216

The FMC216 is an FPGA Mezzanine Card (FMC) per VITA-57 specification. The FMC216 utilizes AD9625 ADCs providing 12-bit conversion rates of up to 2.6 GSPS and a DAC AD9129 providing 14-bit conversion rates of up to 5.6 GSPS.

The analog input/output, clock and trigger interfaces of the FMC216 are routed via SSMC connectors. The internal clock frequency is programmable and the clock is capable of locking to an external reference.

ADC AD9625

12-bit @ 2.6 GSPS

RF PLL Synthesizer

DAC AD9129

14-bit @ 5.6 GSPS

Front Panel



Figure 3: FMC216 Front Panel for option A=0



Figure 4: FMC216 Front Panel for Option A=1

Specifications

Architecture		
Physical	Dimensions	Single module
		Width: 2.71" (69 mm)
		Depth 3.01" (76.5 mm)
Туре	FMC	ADC with DAC and Single FMC
Standards		
FMC	VITA-57	ANSI/VITA 57.1-2008
Configuration		
Power	FMC216	~8W
Environmental	Temperature	Operating temperature: -5° to 55° C (air flow requirements >400 LFM)
		Storage Temperature: -40° to +85°C
	Vibration	1G, 5 to 500 Hz on each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 per cent, non-condensing
Front Panel	Interface Connectors	6x SSMC
	LEDs	User defined and Status
Software Support	Operating System	Agnostic
Conformal Coating		Humiseal 1A33 Polyurethane (Optional)
		Humiseal 1B31 Acrylic (Optional)
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and µTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTM), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA[™] and the AdvancedMC[™] logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

Ordering Options

FMC216 - AB0 - 000 - G0J

A = RF Sampling Clock	G = FMC Board Spacing
0 = Via on Board PLL 1 = Direct RF Sampling	0 = 10 mm (per VITA-57 specification) 1 = 17.5 mm *
B = ADC Speed	
0 = 2.6 GSPS 1 = 2.5 GSPS 2 = 2.0 GSPS	
	J = Temperature Range and Conformal Coating
	0 = Commercial (-5° to $+55^{\circ}$ C), No coating 1 = Commercial (-5° to $+55^{\circ}$ C), Humiseal 1A33 Polyurethane 2 = Commercial (-5° to $+55^{\circ}$ C), Humiseal 1B31 Acrylic 3 = Industrial (-20° to $+70^{\circ}$ C), No coating 4 = Industrial (-20° to $+70^{\circ}$ C), Humiseal 1A33 Polyurethane 5 = Industrial (-20° to $+70^{\circ}$ C), Humiseal 1B31 Acrylic 6 = Extended (-40° to $+85^{\circ}$ C), Humiseal 1A33 Polyurethane** 7 = Extended (-40° to $+85^{\circ}$ C), Humiseal 1B31 Acrylic*

* For use with carriers that require higher mating clearance, such as VadaTech AMC595. Requires full size AMC.

** Conduction cooled, temperature is at edge of module. Consult factory for availability.

Related Products

AMC595



- Xilinx Ultra Scale XCVU440 w/ QorlQ PPC2040
- 8 GB of DDR-4 (single bank of 64-bits)
- FMC support (with special connector)

VPX592



- 3U FPGA carrier for FPGA Mezzanine Card (FMC) per VITA-46 and VITA-57
- Xilinx Kintex UltraScale™ XCKU115 FPGA
- High-performance clock jitter cleaner

FMC229



- FPGA Mezzanine Card (FMC) per VITA 57
- Single DAC39J84
- On board dual Wideband Quadrature Modulator



Contact

VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014 Phone: +1 702 896-3337 | Fax: +1 702 896-0332

Asia Pacific Sales Office

7 Floor, No. 2, Wenhu Street, Neihu District, Taipei 114, Taiwan Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR Phone: +44 2380 016403

info@vadatech.com | www.vadatech.com

Choose VadaTech

We are technology leaders

- First-to-market silicon
- Constant innovation
- Open systems expertise

We commit to our customers

- · Partnerships power innovation
- · Collaborative approach
- Mutual success

We deliver complexity

- · Complete signal chain
- System management
- · Configurable solutions

We manufacture in-house

- Agile production
- · Accelerated deployment
- AS9100 accredited



Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA[™] and the AdvancedMC[™] logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

> © 2017 VadaTech Incorporated, All rights reserved. DOC NO. 4FM737-12 REV 01 | VERSION 1.3 – SEP/17

