

Specifications

Architecture	
Physical	Dimensions Single module Width: 2.71" (69 mm) Depth 3.01" (76.5 mm)
Type	FMC Dual DAC Single FMC slot
Standards	
FMC	Type ANSI/VITA 57.1 - 2008
Configuration	
Power	FMC222 ~6W
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +85°C
	Vibration Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock Operating 30Gs each axis
	Relative Humidity 5 to 95% non-condensing
Front Panel	Interface Connectors 6x MMCX
	LEDs Status
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.