

Specifications

Architecture	
Physical	Dimensions Single Module Width: 2.71" (69 mm) Depth: 3.01" (76.5 mm)
Type	FMC Quad ADC and DAC, Single FMC
Standards	
FMC	Type ANSI/VITA 57.1 - 2008
Configuration	
Power	FMC231 ~10W
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +85°C Vibration 1G to 5-500 Hz on each axis Shock 30Gs each axis Relative Humidity 5 to 95% non-condensing
Front Panel	Interface Connectors 10x SSMC LEDs Status
Software Support	Operating System Agnostic
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.