

Specifications

Architecture		
Physical	Dimensions	Single Module Width 2.71" (69 mm) Depth 3.01" (76.5 mm)
Type	FMC	Dual wideband transceiver, AD9361 FMC connector
Standards		
FMC	VITA 57	ANSI/VITA 57.1-2008
Configuration		
Power	FMC232	3W
Performance	Broadband transmitter	TX EVM: ≤ 40 dB TX noise: ≤ 17 dBm/Hz noise floor TX monitor: ≤ 66 dB dynamic range with 1 dB accuracy
	Integrated synthesizers	2.4 Hz maximum LO step size
Environmental	Temperature	See Ordering Options (air flow requirements >400 LFM) Storage Temperature: -40° to $+85^{\circ}$ C
	Vibration	1G, 5 to 500 Hz on each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	8x SSMC Front Panel Connector
	LEDs	Status
Software Support	Operating System	Agnostic
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty		Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.