

Specifications

Architecture	
Physical	Dimensions Double module, mid-size (full-size optional) Width: 5.85" (148.5 mm) Depth 7.18" (182.6 mm) Weight: 0.3 lbs (136 g)
Type	Analog I/O MicroRTM Single Mezzanine Card Slot
Standards	
MTCA	Type MTCA.4 RTM
Module Management	IPMI IPMI v2.0
Configuration	
Power	MRT575A TBD
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +85°C Vibration Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis Shock 30Gs each axis Relative Humidity 5 to 95% non-condensing
Rear Panel	Interface Connectors Four 9-way Nanonic coax MicroUSB for IPMI LEDs IPMI management control Mechanical Hot swap ejector handle
Software Support	Operating System N/A
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.