

# Specifications

Architecture		
<b>Physical</b>	<b>Dimensions</b>	3U, 1" pitch
Standards		
<b>VPX</b>	<b>Type</b>	VITA 46.0
<b>VPX</b>	<b>Type</b>	VITA 65 OpenVPX
<b>Module Management</b>	<b>IPMI</b>	IPMI v2.0
Configuration		
<b>Power</b>	<b>VPX029</b>	Power Entry Module with 36-75V input 2KVdc Isolation
<b>Front Panel</b>	<b>Micro USB</b>	RS-232 for Health Management
	<b>LEDs</b>	User defined by Health Management
<b>Onboard Interfaces</b>		Dual IPMI Buses
<b>VPX Interfaces</b>	<b>Slot Profiles</b>	See <a href="#">Ordering Options</a>
	<b>Rear IO</b>	Per VITA62 (Fail, Inhibit, Geographic address, etc.)
	<b>Backplane</b>	Connector per VITA 62
Other		
<b>MTBF</b>		MIL Hand book 217-F@ TBD hrs
<b>Certifications</b>		Designed to meet FCC, CE and UL certifications, where applicable
<b>Standards</b>		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
<b>Warranty</b>		Two (2) years, see <a href="#">VadaTech Terms and Conditions</a>

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.