

Specifications

Architecture		
Physical	Dimensions	3U, 1" pitch (for air-cooled version)
Configuration		
Power	VPX100	120W Application specific and MXM module specific (see ordering option)
Bridge	PCIe	Gen4 x16
Front Panel	DP	DP routed to the front or rear (P2)
	Micro USB	Front I/O option RS-232 for Health Management
	LEDs	User defined by Health Management
Onboard Interfaces		MXM
VPX Interfaces	Slot Profiles	See Ordering Options
	Rear IO	16x PCIe Gen4 to P1
	Power Supplies	On P0: VS1 = +12V, +5V, +3.3V
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty		Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.