

# Specifications

Architecture		
Physical	Dimensions	6U, 1" pitch (for air-cooled version)
Configuration		
Power	VPX105	Application specific
PCH		Integrated
Front Panel	FMC	Dual FMC front panels sites
	Micro USB	RS-232 for Health Management
	LEDs	User defined by Health Management
Onboard Interfaces		Dual PMC/XMC site
VPX Interfaces	Slot Profiles	See <a href="#">Ordering Options</a>
	Rear IO	16x PCIe Gen3 (P1 and P2) user I/O J4 to P3/P4 and P5/P6 (VITA 46.9)
	Power Supplies	On P0: VS1 = 12V
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty		Two (2) years, see <a href="#">VadaTech Terms and Conditions</a>

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.