

Specifications

Architecture		
Physical	Dimensions	3U, 1" pitch
Standards		
VPX	Type	VITA 46.x
VPX	Type	VITA 65 OpenVPX
Module Management	IPMI	IPMI v2.0
Configuration		
Power	VPX337	~7W
Front Panel	SSMC	SSMC connector for GPS Antenna, SSMC connector for IRIG AM in, x4 SSMC connectors for clocks in/out
	Micro USB	x3 Micro USB for Serial Interface
	LEDs	IPMI management control, payload power, power good, reset, etc.
VPX Interfaces	Slot Profiles	See Ordering Options
	Rear IO	GbE Muxed onto P1 PCIe or 10GbE on P1
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty	Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.