

Specifications

Architecture		
Physical	Dimensions	6U, 1" pitch
Type	I/O	Six QSFP+ Ports
Configuration		
Power	VPX994	15W
Front Panel	Interface Connectors	QSFP+
	Micro USB	RS-232 from on board CPU NVMRO, *SYSRESET and DISCRETE1 front I/O access Jacks to +12V, +3.3V_AUX, Chassis Ground and Digital Ground
VPX Interfaces	LEDs	CDR Lock LED per port
	Slot Profiles	See Ordering Options
	Rear IO	P0: NVMRO, SYSRESET P1: First 12 ports to QSFP+ P2/P3/P4 ports 0/4/8/12 routed to the QSFP+
	Operating System	Agnostic
Software Support		
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty		Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.