

# Specifications

Architecture		
<b>Physical</b>	<b>Dimensions</b>	3U RTM, 1" pitch
Configuration		
<b>Power</b>	<b>VRT770A</b>	2W (without the M.2 Module)
<b>Rear Panel</b>	<b>Connectors</b>	Micro USB as RS-232 for payload Dual GbE, RJ-45 Micro USB as RS-232 for BMC and IPMI
<b>VPX Interfaces</b>	<b>Slot Profiles</b>	See <a href="#">Ordering Options</a>
	<b>Backplane</b>	RP0: KR loop back RP1: Dual GbE RP2: PCIe to the M.2 storage
	<b>Power Supplies</b>	RP0: VS1 = 12V
Other		
<b>MTBF</b>	MIL Hand book 217-F@ TBD hrs	
<b>Certifications</b>	Designed to meet FCC, CE and UL certifications, where applicable	
<b>Standards</b>	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
<b>Warranty</b>	Two (2) years, see <a href="#">VadaTech Terms and Conditions</a>	

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.